

Gauges HP 700-701-702



Gauges are utilised everywhere when special worth is laid on the exactness of measurement, repeatability and stability. Through the use of high quality materials such as stainless steel can the strength and resistance against aggressive mediums be optimised. Contact Gauges with electric limit contacts are suited to the control and regulation of the process gas pressure.

Order number	Pressure area	Type	Connection	Size
HP700-01	-1 – 1/1,5bar	ND-gauge	1/4" NPT bottom	Ø 63
HP700-02	-1 – 3/5bar	ND-gauge	1/4" NPT bottom	Ø 63
HP700-03	-1 – 6/9bar	ND-gauge	1/4" NPT bottom	Ø 63
HP700-04	-1 – 12/15bar	ND-gauge	1/4" NPT bottom	Ø 63
HP700-20	0 – 200/315bar	ND-gauge	1/4" NPT bottom	Ø 63
HP701-01	-1 – 1/1,5bar	ND-gauge	G 1/4" bottom	Ø 50
HP701-02	-1 – 3/5bar	ND-gauge	G 1/4" bottom	Ø 50
HP701-03	-1 – 6/9bar	ND-gauge	G 1/4" bottom	Ø 50
HP701-04	-1 – 12/15bar	ND-gauge	G 1/4" bottom	Ø 50
HP702-20	0 – 200/315bar	Reed-contact gauge Open / Close	1/4" NPT bottom	Ø 63

Other sizes and combinations on request!

Technical data:

Material:	St, steel 1.4571
Range:	-1 to 315 bar
Accuracy class:	1,6 to DIN 16005
Temperature:	Medium -20°C bis 80°C Environment -25°C bis 60°C

Hornung Quality standard

The company Hornung is certified to **DIN EN ISO 9001**
All single parts are manufactured, assembled and tested in house.
The finished parts are therefore under the criteria of our exact quality control with 100% final control.

Ferdinand Hornung GmbH & Co. KG
Rathenaustraße 55, 63263 Neu-Isenburg

Tel: (0 61 02) 78 83 - 70 www.hornung.org
Fax: (0 61 02) 78 83 - 40 info@hornung.org