


Olive joint connections

HP 710-711-712



HP 710



HP 711



HP 712

Olive joint connections guarantee that all joint connections are tight and torque free. That way dangerous leaks in the pipe system can be eliminated. Olive and screw joint connections can be combined with all products in the HP series.

Order No	Type	Thread	Connection
HP710-03	Straight connection	1/4" NPT	3 mm Tube
HP710-06	Straight connection	1/4" NPT	6 mm Tube
HP710-08	Straight connection	1/4" NPT	8 mm Tube
HP710-10	Straight connection	1/4" NPT	10 mm Tube
HP710-12	Straight connection	1/4" NPT	12 mm Tube
HP711-03	Straight connection	G 1/4"	3 mm Tube
HP711-06	Straight connection	G 1/4"	6 mm Tube
HP711-08	Straight connection	G 1/4"	8 mm Tube
HP711-10	Straight connection	G 1/4"	10 mm Tube
HP711-12	Straight connection	G 1/4"	12 mm Rohr
HP712-03	90° connection	1/4" NPT	3 mm Tube
HP712-06	90° connection	1/4" NPT	6 mm Tube
HP712-08	90° connection	1/4" NPT	8 mm Tube
HP712-10	90° connection	1/4" NPT	10 mm Tube
HP712-12	90° connection	1/4" NPT	12 mm Tube

Other sizes and combinations on request !

Technical data:

Material: St. steel 316
 Operating temp.: -195°C to +200°C

Hornung Quality standard

The company Hornung is certified to **DIN EN ISO 9001**
 All single parts are manufactured, assembled and tested in house.
 The finished parts are therefore under the criteria of our exact quality control with 100% final control.

Ferdinand Hornung GmbH & Co. KG
 Rathenaustraße 55, 63263 Neu-Isenburg

Tel: (0 61 02) 78 83 - 70 www.hornung.org
 Fax: (0 61 02) 78 83 - 40 info@hornung.org